



4000 TLC Floating Dock

LOA:	96.00m
LENGTH OF PONTOON:	90.00m
LENGTH OVER KEEL BLOCKS:	87.60m
LENGTH OF SIDEWALLS:	90.00m
BREADTH (MOULDED):	30.00m
BREADTH (INSIDE DOCK):	23.00m
WIDTH OF SIDEWALLS:	3.50m
DISTANCE FROM TOP DECK TO BASELINE:	14.00m
DISTANCE FROM SAFETY DECK TO BASELINE:	11.00m
DEPTH OF PONTOON AT CENTRE-LINE:	3.70m
DEPTH OF PONTOON AT INSIDE DOCK:	3.60m
MAX. IMMERSION DRAFT:	11.50m
DRAFT ABOVE KEEL BLOCKS WHEN MAX. IMMERSION DRAFT:	6.60m
WORKING DRAFT:	3.30m
HEIGHT OF KEEL BLOCKS:	1.20m
SPACE OF KEEL BLOCKS:	1.20m
FRAME SPACING:	0.60m
MAXIMUM LIFTING CAPACITY:	3500t
LIFLING TIME FOR VESSEL OF 4000t WEIGHT:	abt.120min
CRANE:	10t/7m - 10t/25m x 3sets
PUMP CAPACITY:	1250m ³ /h x 4sets

Details given in good faith and are believed to be correct but not guaranteed.

For any enquiry, please drop us a email at marketing@amsbach.com.sg.